

1 UNITED STATES COURT OF APPEALS

2 FOR THE SECOND CIRCUIT

3 August Term, 2002

4 (Argued: March 7, 2003

Decided: August 6, 2003)

5
6 Docket No. 02-4237

7 -----
8 PUBLIC CITIZEN, INC., NEW YORK PUBLIC INTEREST RESEARCH GROUP,
9 THE CENTER FOR AUTO SAFETY,

10 Petitioners,

11 - v. -

12 NORMAN MINETA, Secretary of Transportation,

13 Respondent,

14 ALLIANCE OF AUTOMOBILE MANUFACTURERS,

15 Intervenor.
16 -----

17 Before: CARDAMONE and SACK, Circuit Judges, and PAULEY,
18 District Judge.*

19 The petitioners seek review of the Final Rule on Tire
20 Pressure Monitoring Systems, 67 Fed. Reg. 38704 (2002), adopting
21 Federal Motor Vehicle Safety Standard No. 138, 49 C.F.R.
22 § 571.138 (2002), which was issued by the Secretary of
23 Transportation to regulate the installation of tire pressure
24 monitoring systems in new motor vehicles. We conclude that the
25 rule was both contrary to law and arbitrary and capricious.

* The Honorable William H. Pauley III, of the United States District Court for the Southern District of New York, sitting by designation.

1 Accordingly, we grant the petition for review, vacate the rule,
2 and remand for further rulemaking proceedings.

3 Petition granted; rule vacated; remanded.

4 ALLISON M. ZIEVE, Public Citizen
5 Litigation Group (Scott L. Nelson and
6 David C. Vladeck, of counsel),
7 Washington, D.C., for Petitioners.

8 H. THOMAS BYRON III, Department of
9 Justice, Civil Division, Appellate Staff
10 (Robert D. McCallum, Jr., Assistant
11 Attorney General of the United States,
12 Douglas N. Letter, Department of
13 Justice, Civil Division, Appellate
14 Staff, of counsel), Washington, D.C.,
15 for Respondent.

16 ERICA Z. JONES, Mayer, Brown, Rowe & Maw
17 (Adam Sloane and David M. Gossett, of
18 counsel), Washington, D.C., for
19 Intervenor.

20 Roger C. Fairchild (Charles H. Lockwood,
21 II, of counsel), Purcellville, VA,
22 submitted a brief for Amicus Curiae
23 Association of International Automobile
24 Manufacturers, Inc.

25 SACK, Circuit Judge:

26 The petitioners, three not-for-profit advocacy
27 organizations, Public Citizen, Inc., New York Public Interest
28 Research Group, and the Center for Auto Safety, petition for
29 review of the Final Rule on Tire Pressure Monitoring Systems, 67
30 Fed. Reg. 38704 (2002), adopting Federal Motor Vehicle Safety
31 Standard No. 138, 49 C.F.R. § 571.138 (2002), which was issued by
32 the Secretary of Transportation to regulate the installation of
33 tire pressure monitoring systems in new motor vehicles. The
34 petitioners argue that the rule is contrary to the intent of

1 Congress when it enacted section 13 of the Transportation Recall
2 Enhancement, Accountability, and Documentation Act, Pub. L. No.
3 106-414, § 13, 114 Stat. 1800, 1806 (2000), reprinted in 49
4 U.S.C. § 30123 note (2003), and arbitrary and capricious under
5 the Administrative Procedure Act, Pub. L. No. 89-554, 80 Stat.
6 393 (1966) (codified at 5 U.S.C. § 706 (1996)) ("APA"). The rule
7 gives automakers the discretion to comply with either a four-
8 tire, 25 percent or a one-tire, 30 percent under-inflation
9 standard. According to the rulemaking record, (1) the one-tire
10 standard allows automakers to install tire pressure monitoring
11 systems that fail to warn drivers in approximately half of the
12 instances in which tires are significantly under-inflated, and
13 (2) the four-tire, 25 percent standard would prevent more
14 injuries, save more lives, and be more cost-effective. We
15 conclude that the rule is both contrary to the intent of the
16 TREAD Act and arbitrary and capricious under the APA. We
17 therefore grant the petition for review, vacate the rule, and
18 remand for further rulemaking proceedings.

19 **BACKGROUND**

20 This petition involves a complex web of statutes,
21 regulatory actions, public comments, and factual findings whose
22 history spans several decades.

23 The Safety Act

24 In 1966, Congress enacted the National Traffic and
25 Motor Vehicle Safety Act. See National Traffic and Motor Vehicle
26 Safety Act of 1966, Pub. L. No. 89-563, 80 Stat. 718 (codified at

1 15 U.S.C. § 1381 et seq. (1966), repealed and reenacted, without
2 relevant changes, as the National Highway Traffic Safety
3 Administration Authorization Act of 1991, and recodified as
4 amended at 49 U.S.C. § 30101 et seq. (1994)) ("Safety Act"). The
5 purpose of the Safety Act is "to reduce traffic accidents and
6 deaths and injuries resulting from traffic accidents . . . [by]
7 prescrib[ing] motor vehicle safety standards . . . [and]
8 carry[ing] out needed safety research and development." 49
9 U.S.C. § 30101. To achieve these objectives, the Safety Act
10 provides that "[t]he Secretary of Transportation shall prescribe
11 motor vehicle safety standards," and that "[e]ach standard shall
12 be practicable, meet the need for motor vehicle safety, and be
13 stated in objective terms." Id. § 30111(a). When issuing
14 standards under the Safety Act, the Secretary must consider the
15 "relevant available motor vehicle safety information," "whether
16 [the] proposed standard is reasonable, practicable, and
17 appropriate" for the relevant motor vehicle types, and "the
18 extent to which the standard will carry out" the purposes of the
19 Safety Act. Id. § 30111(b). Since 1980, the Secretary's general
20 authority to promulgate standards under the Safety Act has been
21 delegated to the Administrator of the National Highway Traffic
22 Safety Administration ("NHTSA"). 49 C.F.R. § 1.50(a) (2003); 45
23 Fed. Reg. 83407 (1980).¹

¹ We use the terms "NHTSA" and "the agency" interchangeably when referring to the Secretary of Transportation and the Administrator of the National Highway Traffic and Safety Administration.

1 The Advance Notice of Proposed Rulemaking

2 On January 26, 1981, NHTSA published an Advance Notice
3 of Proposed Rulemaking soliciting public comment on whether the
4 agency should propose a new safety standard requiring automakers
5 to install "low tire pressure warning devices" in new motor
6 vehicles, in order to improve fuel economy, extend tire life, and
7 prevent motor-vehicle crashes. Advance Notice of Proposed
8 Rulemaking on Low Tire Pressure Warning Devices, 46 Fed. Reg.
9 8062 (1981). The agency explained that two different types of
10 low pressure warning devices were then available: "in-vehicle"
11 devices, which had a monitor in each tire that relayed
12 information to a dashboard display, and "on-tire" devices, which
13 consisted of a red warning-signal that was attached to the valve
14 stem of each tire, and was designed to protrude when a tire
15 became significantly under-inflated. Id. The agency sought
16 public comment on the costs, benefits, and reliability of the two
17 types of devices.

18 In August 1981, the agency concluded that in-vehicle
19 warning devices were too expensive and on-tire warning devices
20 were too inaccurate to justify proposing or adopting
21 requirements. The agency therefore terminated the rulemaking
22 proceedings. Notice of Termination of Rulemaking on Low Tire
23 Pressure Warning Devices, 46 Fed. Reg. 43721 (1981) ("Notice of
24 Termination").²

² The agency nonetheless noted that "[m]aintaining proper tire inflation pressure results in direct savings to drivers in

1 The TREAD Act

2 During the 1990s, NHTSA received a series of complaints
3 regarding tread separation in two models of Bridgestone/Firestone
4 tires installed on Ford Explorers. Advance Notice of Proposed
5 Rulemaking on Standards Enforcement, Defect Investigation, Defect
6 and Noncompliance Reports, and Record Retention, 66 Fed. Reg.
7 6532, 6533 (2001) ("Standards Enforcement"); Notice of Proposed
8 Rulemaking on Tire Pressure Monitoring Systems, 66 Fed. Reg.
9 38982, 38989 n.13 (2001) ("Notice"). In May 2000, NHTSA opened a
10 defect investigation into the matter; a few months later,
11 Bridgestone/Firestone and Ford recalled over 14 million tires.
12 Standards Enforcement, 66 Fed. Reg. at 6533; Notice, 66 Fed. Reg.
13 at 38989 n.13. In September 2000, Congress held hearings to
14 investigate the events leading to the tire recall and to consider
15 formulating a legislative response. See S. Rep. No. 106-423, at
16 2-3 (2000).

17 On November 1, 2000, the Transportation Recall
18 Enhancement, Accountability, and Documentation Act was enacted.
19 See Pub. L. No. 106-414, 114 Stat. 1800 (2000) (codified at 49
20 U.S.C. § 30101 et seq. (2003)) ("TREAD Act"). The TREAD Act
21 addresses several issues raised by the Ford/Firestone tire
22 recall, such as defect reporting requirements, see 49 U.S.C.
23 § 30166, enforcement measures, see 49 U.S.C. §§ 30165, 30170, and

terms of better gas mileage and longer tire life, as well as
offering increased safety." Notice of Termination, 46 Fed. Reg.
at 43721.

1 "significantly under inflated" tires, see TREAD Act § 13. For
2 present purposes, only section 13 of the TREAD Act, which
3 addresses the issue of significantly under-inflated tires, is
4 relevant. It provides:

5 Not later than 1 year after the date of
6 enactment of this Act [i.e., not later than
7 November 1, 2001], the Secretary of
8 Transportation shall complete a rulemaking
9 for a regulation to require a warning system
10 in new motor vehicles to indicate to the
11 operator when a tire is significantly under
12 inflated. Such requirement shall become
13 effective not later than 2 years after the
14 date of the completion of such rulemaking.

15 TREAD Act § 13.

16 NHTSA's Research Findings

17 Shortly before the TREAD Act became law, NHTSA resumed
18 research studies and rulemaking proceedings on tire pressure
19 warning devices. In September 2000, the Bureau of Transportation
20 Statistics ("BTS") completed a survey of drivers in order to
21 assess the extent to which drivers monitor tire pressure levels.
22 Id. at 38713. The BTS survey asked drivers: "How often do you,
23 or the person who checks your tires, check the air pressure in
24 your tires?" Id. Seventy-one percent of the respondents claimed
25 that they checked the vehicle's tire pressure levels less than
26 once per month. Id.³

³ The agency noted that "it seems likely that the respondents . . . overstated the frequency with which they check tire pressure, particularly given the fact that these surveys were conducted during the height of publicity about tire failures on sport utility vehicles in . . . late 2000 and early 2001." Final Rule, 67 Fed. Reg. at 38713 n.17.

1 In February 2001, NHTSA's National Center for
2 Statistics and Analysis ("NCSA") conducted a random survey of
3 motor vehicles and drivers in order to assess the extent to which
4 tires are "significantly under-inflated" -- i.e., the extent to
5 which actual tire pressures fall significantly below recommended
6 levels. Final Rule on Tire Pressure Monitoring Systems, 67 Fed.
7 Reg. 38704, 38713, 38718 (2002) ("Final Rule"). To make these
8 assessments, the NCSA measured the air pressure on the tires of
9 approximately 10,000⁴ passenger cars and light trucks, and
10 compared those actual tire pressures to the vehicle
11 manufacturer's recommended cold inflation pressure for the
12 vehicle's tires, i.e., the "placard pressure." Id. at 38705
13 (defining "placard pressure"); id. at 38713, 38718 (explaining
14 the NCSA survey methods).

15 The NCSA survey produced the following findings:

16 (1) about 36 percent of the passenger cars
17 and 40 percent of the light trucks surveyed
18 had at least one tire that was 20 percent
19 under-inflated, id. at 38713;

20 (2) about 26 percent of the passenger cars
21 and 29 percent of the light trucks surveyed
22 had at least one tire that was 25 percent
23 under-inflated, id.;

24 (3) about 20 percent of the passenger cars
25 and 20 percent of the light trucks surveyed

⁴ The record does not clearly state how many vehicles were surveyed by the NCSA. Compare Final Rule, 67 Fed. Reg. at 38713 (stating that 11,530 vehicles were surveyed, including 6,442 passenger cars, 1,874 sports utility vehicles (SUVs), 1,376 vans, and 1,838 pick-up trucks), and id. at 38713 n.18 (defining SUVs, vans, and pick-up trucks as "light trucks"), with id. at 38718 (stating that 9,917 vehicles were surveyed, including 5,967 passenger cars and 3,950 light trucks).

1 had at least one tire that was 30 percent
2 under-inflated, id. at 38718; and

3 In May 2001, NHTSA's Vehicle Research and Test Center
4 ("VRTC") completed a series of performance and cost studies on
5 available tire pressure warning devices. Id. at 38708, 38715 &
6 n.27. These studies revealed that during the two decades
7 following the termination of NHTSA's earlier rulemaking
8 proceedings, the technology of tire pressure warning devices had
9 substantially improved. Notice, 66 Fed. Reg. at 38987; Final
10 Rule at 38715. In-vehicle and on-tire warning devices had become
11 obsolete, and had been replaced by two new technologies: "direct"
12 and "indirect" tire pressure monitoring systems ("TPMSs").
13 Notice, 66 Fed. Reg. at 38986-88; Final Rule, 67 Fed. Reg. at
14 38705, 38715-16.

15 NHTSA described the basic characteristics of direct and
16 indirect TPMSs as follows:

17 A. Indirect TPMSs

18 Current indirect TPMSs work with a vehicle's
19 ABS [anti-lock braking system]. The ABS
20 employs wheel speed sensors to measure the
21 rotational speed of each of the four wheels.
22 As a tire's pressure decreases, the rolling
23 radius decreases, and the rotational speed of
24 that wheel increases correspondingly. Most
25 current indirect TPMSs compare the sums of
26 the wheel speeds on each diagonal (i.e., the
27 sum of the speeds of the right front and left
28 rear wheels as compared to the sum of the
29 speeds of the left front and right rear
30 wheels). Dividing the difference of the sums
31 by the average of the four wheels [sic]
32 speeds allows the indirect TPMS to have a
33 ratio that is independent of vehicle
34 speed. . . . If this ratio deviates from a
35 set tolerance, one or more tires must be

1 over- or under-inflated. A telltale then
2 indicates to the driver that a tire is
3 under-inflated. However, the telltale cannot
4 identify which tire is under-inflated. . . .

5 B. Direct TPMSs

6 Direct TPMSs use pressure sensors, located in
7 each wheel, to directly measure the pressure
8 in each tire. These sensors broadcast
9 pressure data via a wireless radio frequency
10 transmitter to a central receiver. The data
11 are then analyzed and the results sent to a
12 display mounted inside the vehicle. The type
13 of display varies from a simple telltale,
14 which is how most vehicles are currently
15 equipped, to a display showing the pressure
16 in each tire, sometimes including the spare
17 tire. Thus, direct TPMSs can be linked to a
18 display that tells the driver which tire is
19 under-inflated.

20 Final Rule, 67 Fed. Reg. at 38716; see also Notice, 66 Fed. Reg.
21 at 38987-88.

22 The VRTC's performance and cost studies revealed
23 significant differences between direct and indirect systems. In
24 performance terms, direct systems enjoyed two major advantages
25 over indirect systems, enabling them to detect a broader range of
26 under-inflation than indirect systems.

27 First, whereas direct systems are able to detect all
28 under-inflation levels equal to or greater than 20 percent,
29 indirect systems can detect only those under-inflation levels
30 equal to or greater than 30 percent.⁵ Notice, 66 Fed. Reg. at

⁵ In the Final Rule, NHTSA once mentioned that this statement only held true of "most" of the indirect systems that the agency tested, Final Rule, 67 Fed. Reg. at 38716, and that "one" of those indirect systems -- the Continental Teves indirect TPMS on the BMW M3 -- could detect levels of under-inflation between 9 and 21 percent, id. at 38716 n.29. But the agency apparently considered this exception to be insignificant. In all

1 38988-89; Final Rule, 67 Fed. Reg. at 38708. Second, because
2 direct systems operate by measuring each tire's pressure, they
3 can detect under-inflation when it occurs in any one of the
4 vehicle's tires, or in any combination of the vehicle's tires.
5 Notice, 66 Fed. Reg. at 38988; Final Rule, 67 Fed. Reg. at 38716,
6 38718. Indirect systems, by contrast, operate by comparing the
7 sums of the wheel speeds in diagonally opposed tires. Final
8 Rule, 67 Fed. Reg. at 38716. As a result, indirect systems
9 cannot detect under-inflation when it occurs simultaneously (and
10 roughly equally⁶) in (1) all four of the vehicle's tires, (2) two
11 tires on the same side of the vehicle, or (3) two tires on the
12 same axle of the vehicle. Notice, 66 Fed. Reg. at 38987; Final
13 Rule, 67 Fed. Reg. at 38716, 38718. As the agency explained,
14 these three combinations of significantly under-inflated tires
15 occurred "frequently" in the passenger cars and light trucks
16 randomly surveyed by the NCSA, suggesting that indirect systems
17 are substantially less effective than direct systems. Final

other instances, the agency stated the 30 percent limitation of indirect systems in absolute terms, without mentioning the Continental Teves indirect TPMS. See, e.g., Notice, 66 Fed. Reg. at 38989; Final Rule, 67 Fed. Reg. at 38708, 38718. In any event, like all other indirect systems, the Continental Teves TPMS could not detect under-inflation that occurred simultaneously in all four tires, or in two tires on the same side or the same axle of the vehicle. Final Rule, 67 Fed. Reg. at 38725 n.61. See infra note 5 and accompanying text.

⁶ By under-inflation that occurs "roughly equally," we mean instances of under-inflation in which "the difference in the tire pressures is not 30 percent or greater." Final Rule, 67 Fed. Reg. at 38718. When there is a difference between the tire pressures of two tires that is 30 percent or greater, indirect systems are able to detect it. See id.

1 Rule, 67 Fed. Reg. at 38718. Indeed, the agency concluded that
2 indirect systems "would have provided a warning in only about 50
3 percent of the instances" in which NHTSA found significantly
4 under-inflated tires, id., while direct systems "would have
5 provided warnings in all [of] those instances," id.

6 The agency also found that direct systems have several
7 other advantages over indirect systems: (1) Direct systems can
8 detect much smaller pressure losses than can indirect systems;
9 (2) direct systems can indicate which tire is under-inflated,
10 whereas indirect systems can indicate only that one or more tires
11 is under-inflated; (3) unlike direct systems, indirect systems
12 produce false positives when one of the vehicle's tires is
13 mismatched, out of balance, or out of alignment, or when the
14 vehicle is driven on gravel or bumpy roads, or at speeds greater
15 than 70 miles per hour; (4) direct systems can detect under-
16 inflated tires in stationary or moving vehicles, whereas indirect
17 systems can detect under-inflated tires only in moving vehicles;
18 (5) direct systems can detect pressure losses almost instantly,
19 whereas indirect systems do not detect pressure losses until
20 several minutes after tires become significantly under-inflated;
21 (6) direct systems need not be calibrated, whereas indirect
22 systems need to be calibrated when the vehicle is first driven,
23 and recalibrated when a tire is inflated, rotated, or changed,
24 and do not function properly while they are being calibrated.
25 See generally Notice, 66 Fed. Reg. at 38987-88; cf. Final Rule,
26 67 Fed. Reg. at 38728 (explaining the "time frame" within which

1 TPMSs must warn drivers that tires are significantly under-
2 inflated); id. at 38730 (declining to require "calibration
3 indicators" in TPMSs).

4 In cost terms, indirect systems are less expensive to
5 install in vehicles equipped with ABS, Notice, 66 Fed. Reg. at
6 38987-88; Final Rule, 67 Fed. Reg. at 38706, 38725, 38740, but
7 direct systems are less expensive to install in vehicles that are
8 not equipped with ABS, Notice, 66 Fed. Reg. at 38988; Final Rule,
9 67 Fed. Reg. at 38740.⁷ In the 2000 model year, about 67 percent
10 of all new light vehicles were equipped with ABS. Final Rule, 67
11 Fed. Reg. at 38740. As a result, the agency estimated that, "for
12 vehicles already equipped with ABS, the installation of a current
13 indirect TPMS is the least expensive way of complying with a TPMS
14 standard." Id. at 38706; see id. at 38725.

15 In July 2001, the BTS conducted a follow-up survey of
16 drivers in order to estimate the effect that installing indirect
17 or direct TPMSs would have upon the behavior of drivers. Id. at
18 38718. The follow-up survey indicated that if TPMSs were
19 installed in increasing numbers of new motor vehicles, "65
20 percent of drivers would be less concerned, to a great extent or
21 a very great extent, with routinely maintaining" the tire

⁷ The different installation costs of indirect and direct systems arise from the fact that indirect systems rely upon data collected by a vehicle's ABS, whereas direct systems do not. Final Rule, 67 Fed. Reg. at 38705, 38716. Thus, in order to install an indirect system into a vehicle that is not equipped with ABS, an automaker would first need to install four wheel speed sensors, at a cost of \$130 per vehicle, or a fully equipped ABS, at a cost of \$240 per vehicle. Id. at 38740.

1 pressure in those vehicles. Id. at 38718; see id. at 38727.
2 NHTSA later acknowledged that, "given the performance limitations
3 of indirect TPMSs," id. at 38728 (emphasis added), "[t]his
4 substantial shift in reliance from routine maintenance to TPMS
5 concerns the agency," id. at 38727-28, because it threatens to
6 instill "a false sense of security" in drivers of vehicles that
7 rely upon indirect systems, id. at 38728.

8 The Notice of Proposed Rulemaking

9 On July 26, 2001, NHTSA published a Notice of Proposed
10 Rulemaking proposing to establish a standard for low tire
11 pressure warning devices under the authority of the Safety Act
12 and section 13 of the TREAD Act. Notice, 66 Fed. Reg. at 38982.
13 In this notice, NHTSA advanced two alternative proposals for a
14 new safety standard. Id.; Final Rule, 67 Fed. Reg. at 38708.
15 The agency planned to adopt one of the two proposals in the Final
16 Rule. Final Rule, 67 Fed. Reg. at 38705.

17 The two proposals were known respectively as the "four-
18 tire, 20 percent" and "three-tire, 25 percent" alternatives.
19 Final Rule, 67 Fed. Reg. at 38705. As the names suggest, the two
20 proposals differed in two important respects: the level of under-
21 inflation that they regarded as "significant," and the number of
22 under-inflated tires that they required TPMSs to be able to
23 detect at any one time. Id. The first, more rigorous standard
24 would require TPMSs to warn drivers when the tire pressure in one
25 or more tires, up to a total of four tires, fell 20 percent or
26 more below the placard pressure, or to a minimum level of

1 pressure to be specified in the new standard, whichever tire
2 pressure was higher. Notice, 66 Fed. Reg. at 38982-83, 38989;
3 Final Rule, 67 Fed. Reg. at 38705, 38708. The second, more
4 relaxed standard would require TPMSs to warn drivers when the
5 tire pressure in one or more tires, up to a total of three tires,
6 fell 25 percent or more below the placard pressure, or a minimum
7 level of pressure to be specified in the new standard, whichever
8 tire pressure was higher. Notice, 66 Fed. Reg. at 38982-83,
9 38989; Final Rule, 67 Fed. Reg. at 38705, 38708. Thus, the
10 second, three-tire standard would not require a warning when the
11 tire pressure fell in all four of the vehicle's tires
12 simultaneously and in roughly equal proportions. "In most other
13 respects, the two alternatives were identical." Final Rule, 67
14 Fed. Reg. at 38708; see also Notice, 66 Fed. Reg. 38989 (listing
15 the common aspects of the two standards).

16 With respect to these two standards, the agency made
17 the following findings: (1) currently available direct systems
18 could satisfy both standards; (2) currently available indirect
19 systems could not satisfy either standard; and (3) "upgraded"
20 indirect systems -- which had not yet been planned, developed, or
21 produced -- would be able to satisfy the more relaxed, three-
22 tire, 25 percent standard, but not the more rigorous, four-tire,
23 20 percent standard. See Notice, 66 Fed. Reg. at 38989; Final
24 Rule, 67 Fed. Reg. at 38708.

25 In addition, the agency predicted that if the three-
26 tire, 25 percent standard were adopted, automakers would minimize

1 compliance costs by installing improved indirect systems in
 2 vehicles with ABS and direct systems in vehicles without ABS.
 3 Notice, 66 Fed. Reg. at 38983; Final Rule, 67 Fed. Reg. at 38708.
 4 The agency specifically requested public comments on whether this
 5 goal would be "practicable." Notice, 66 Fed. Reg. at 38989.

6 The agency also requested comments on "whether vehicle
 7 manufacturers [would] be able to meet the statutory deadline, and
 8 whether TPMS manufacturers [would] be able to supply enough TPMSs
 9 to meet the demand," id. at 38997, and if not, whether it would
 10 be "appropriate" to introduce the new safety standards during a
 11 "phase-in" period, id.⁸

12 Finally, NHTSA included a cost/benefit analysis that
 13 may be summarized as follows:

	Four-tire, 20 percent	Three-tire, 25 percent
Fatalities prevented per year ⁹	79	49
Injuries mitigated or prevented per year ¹⁰	10,635	6,585

⁸ A "phase-in period" is a period of lead time during which the agency gradually increases the percentage of motor vehicles that must comply with new safety standards. See, e.g., Notice, 66 Fed. Reg. at 38997; Final Rule, 67 Fed. Reg. at 38738.

⁹ In the Notice of Proposed Rulemaking, the agency's benefit estimates included only the number of deaths and injuries prevented due to reductions in stopping distances. In the Final Rule, the agency's benefit estimates also included the number of deaths and injuries prevented due to reductions in crashes caused by blowouts and skidding/loss of control. Compare Notice, 66 Fed. Reg. at 38996, with Final Rule, 67 Fed. Reg. at 38708 n.6.

¹⁰ See supra note 9.

1	Average net cost per vehicle ¹¹	\$23.08	\$8.63
2	Total net cost per year ¹² (millions)	\$369	\$138
3	Net cost per equivalent life saved ¹³	\$1.9	\$1.1
4	(millions)		_____

5 Notice, 66 Fed. Reg. at 38996-97; Final Rule, 67 Fed. Reg. at
6 38708-09.

7 Public Comments on Hybrid Systems

8 In public comments on the proposed rule, TRW Automotive
9 Electronics, a manufacturer of direct and indirect systems,
10 indicated that it could meet the requirements of the second,
11 three-tire, 25 percent standard by creating "hybrid" systems,
12 which would be made from the components of direct and indirect
13 systems. See Final Rule, 67 Fed. Reg. at 38716. TRW explained
14 that hybrid systems could be produced by installing a radio
15 transmitter and two direct tire-pressure sensors in new motor
16 vehicles already equipped with indirect systems. Id.

¹¹ "Net costs included . . . vehicle costs minus . . . fuel savings and . . . tread wear savings. These cost estimates did not include maintenance costs. For [the] final rule, the agency . . . estimated maintenance costs." Final Rule, 67 Fed. Reg. at 38708 n.6; see also id. at 38709 n.7.

¹² See supra note 11.

¹³ See supra notes 9 and 11. Although the record does not explain how the agency calculated "net cost per equivalent life saved," it seems that the agency first assigned some number of "injuries prevented" to be "equivalent" to one "life saved," and then added the "actual" and "equivalent" lives saved by each standard, which yielded the number of "equivalent lives saved" by each standard. Finally, the agency divided the "total annual net cost" of each standard by the number of "equivalent lives saved" by each standard, which yielded the "net cost per equivalent life saved" of each standard. See generally Final Rule, 67 Fed. Reg. at 38740-41.

1 The agency thought that such hybrid systems would be
2 able to overcome the limits of current indirect systems by
3 detecting under-inflation equal to or greater than 25 percent,
4 and by detecting under-inflation when it occurred in any
5 combination of the vehicle's tires. Id. at 38716, 38740. But
6 TRW stated that it was not planning to produce hybrid systems,
7 id. at 38706; see also id. at 38715, 38716, 38740, and that it
8 might be unable to produce them by November 1, 2003, id. at
9 38725. In light of these comments, the agency acknowledged that
10 it did not know when such systems could be produced. Id. at
11 38715, 38716.

12 The Draft Final Rule

13 On December 18, 2001, the agency submitted a draft
14 final rule to the federal Office of Management and Budget ("OMB")
15 for review.¹⁴ Final Rule, 67 Fed. Reg. at 38711-12. The draft
16 final rule specified short-term and long-term requirements. The
17 short-term requirements applied only during a phase-in period
18 between November 1, 2003, and November 1, 2006; the long-term
19 requirements applied thereafter. Id. at 38712.

20 During the phase-in period, new vehicles would be
21 permitted to comply with one of two standards. The two standards
22 were not the same as those previously proposed. The first was a
23 "four-tire, 25 percent" standard; the second was a less rigorous

¹⁴ Like all federal administrative agencies, NHTSA is required to submit a draft of any "significant" regulatory action to the OMB for review. Exec. Order No. 12,866, 58 Fed. Reg. 51735 (Sept. 30, 1993).

1 "one-tire, 30 percent" standard. Id. at 38712, 38717. The first
2 would have required TPMSs to warn drivers when the tire pressure
3 in one or more tires, up to a total of four tires, fell 25
4 percent or more below the placard pressure, or to a minimum level
5 of pressure to be specified in the new standard, whichever tire
6 pressure was higher. Id. The second would have required TPMSs
7 to warn drivers when the tire pressure in one tire fell 30
8 percent or more below the placard pressure, or to a minimum level
9 of pressure to be specified in the new standard, whichever tire
10 pressure was higher. Id. In other words, the second, one-tire
11 standard would not have required a warning when the tire pressure
12 fell in two, three, or four of the vehicle's tires
13 simultaneously, and in roughly equal proportions -- i.e., in
14 "approximately half" of the cases in which vehicles have
15 significantly under-inflated tires. Id. at 38728; see also id.
16 at 38718 ("These combinations of significantly under-inflated
17 tires occur frequently enough that current indirect TPMSs would
18 have provided a warning in only about 50 percent of the instances
19 in which NHTSA found significant under-inflation in the February
20 2001 NCSA survey."). After the phase-in period, the one-tire, 30
21 percent option would be terminated, and the four-tire, 25 percent
22 option would be mandatory for all new vehicles. Id. at 38712,
23 38718.

24 The agency explained the new aspects of the draft final
25 rule as follows:

1 The agency created the one-tire, 30 percent
2 option so that vehicle manufacturers could
3 continue to install current indirect TPMSs
4 for several more years, thus providing
5 additional time and flexibility for
6 innovation and technological development.
7 The agency created the other option by
8 adjusting the definition of "significantly
9 under-inflated" for the four-tire option to
10 25 percent (instead of 20 percent) so that
11 improved indirect TPMSs and hybrid TPMSs
12 could be used to comply with the TPMS
13 standard.

14 Id. at 38717-18.

15 The OMB Return Letter

16 On February 12, 2002, after reviewing the draft final
17 rule, OMB returned it to NHTSA for reconsideration, along with a
18 letter explaining its reasons for doing so. See generally Final
19 Rule, 67 Fed. Reg. at 38712, 38718 (describing the OMB return
20 letter). In the letter, OMB argued that NHTSA should base the
21 final rule on "overall vehicle safety" concerns, rather than
22 limiting itself to "tire safety" concerns. Id. at 38712.
23 Specifically, OMB urged NHTSA "to consider the impact of
24 regulatory alternatives on the availability of anti-lock brake
25 systems (ABS)." OMB Return Letter of Feb. 12, 2002, at 1.¹⁵ OMB
26 predicted that if NHTSA adopted the more relaxed one-tire, 30
27 percent standard as a long-term requirement, it would provide
28 automakers with an additional incentive to install ABS in new
29 motor vehicles, and accelerate the rate of adoption of ABS. OMB

¹⁵ The full text of the OMB's return letter is available at http://www.whitehouse.gov/omb/inforeg/return_letter.html (last visited August 6, 2003).

1 Return Letter at 2. OMB claimed that "[b]oth experimental
2 evidence and recent real-world data have indicated a modest net
3 safety benefit from anti-lock brakes." Id.

4 The Final Rule

5 On June 5, 2002, NHTSA published the Final Rule that is
6 the subject of the instant petition for review. Final Rule, 67
7 Fed. Reg. at 38704. NHTSA rejected OMB's criticisms on three
8 grounds: (1) Although the Safety Act generally requires NHTSA to
9 improve overall vehicle safety, the TREAD Act specifically
10 requires NHTSA to improve tire safety, id. at 38718; (2) there
11 was "no reliable basis" to conclude that permitting automakers to
12 install current indirect systems would lead to a significant
13 increase in the installation of ABS, id. at 38719;¹⁶ and (3)
14 there was "no statistically reliable basis for concluding that
15 ABS reduces fatalities," id., and thus there was no reason to
16 encourage the installation of ABS in new vehicles.

17 Like the draft final rule, the Final Rule is divided
18 into two parts. The first part includes the rule's short-term
19 requirements, which are substantially the same as the short-term
20 requirements described in the earlier draft. The short-term
21 requirements give automakers the discretion to comply with either

¹⁶ The agency rejected this hypothesis because (1) "the final rule does not mandate the installation of ABS," Final Rule, 67 Fed. Reg. at 38719; (2) the record evidence does not suggest that automakers would voluntarily install ABS, id.; and (3) it would be economically unreasonable for automakers to install ABS, insofar as it would mean spending "\$240 per vehicle to install ABS" in order "to save \$53, the difference between the cost of a direct TPMS (\$66) and an indirect TPMS (\$13)," id.

1 a four-tire, 25 percent standard, or a one-tire, 30 percent
2 standard. Federal Motor Vehicle Safety Standard No. 138, 49
3 C.F.R. § 571.138 pt. S4.2 (2002) ("Safety Standard"); Final Rule,
4 67 Fed. Reg. 38722-23. These requirements apply only during the
5 phase-in period between November 1, 2003, and October 31, 2006.
6 Safety Standard, 49 C.F.R. § 571.138 pt. S4.2; Final Rule, 67
7 Fed. Reg. at 38722, 38738. During each year of the phase-in
8 period, automakers would be required to install TPMSs in
9 increasing percentages of new motor vehicles: 10 percent of
10 vehicles during the first year; 35 percent of vehicles during the
11 second year; 65 percent of vehicles during the third year.
12 Safety Standard, 49 C.F.R. § 571.138 pt. S7; Final Rule, 67 Fed.
13 Reg. at 38738. After October 31, 2006, the long-term
14 requirements would be mandatory for 100 percent of new motor
15 vehicles. Final Rule, 67 Fed. Reg. at 38738.

16 The long-term requirements -- which had been the four-
17 tire, 25 percent standard in the draft final rule -- are not,
18 however, included in the Final Rule. "To allow for the
19 consideration of additional data regarding the requirements for
20 vehicles manufactured after October 31, 2006," the agency has
21 left the long-term requirements unspecified, kept "the rulemaking
22 docket open for the submission of new data and analyses," id. at
23 38722, and invited commenters to "address how the performance
24 characteristics of particular types of TPMSs satisfy the [TREAD
25 Act's] requirement that systems provide a warning 'when a tire is
26 significantly under-inflated,'" id.; see also id. at 38704. The

1 agency has also announced a plan to "conduct a study comparing
2 the tire pressures of vehicles without any TPMS to the pressures
3 of vehicles with TPMSs, especially TPMSs that do not comply with
4 the four-tire, 25 percent compliance option." Id. at 38704,
5 38722, 38738.

6 NHTSA noted that, "[b]ased on the record now before the
7 agency, NHTSA tentatively believes that the four-tire, 25 percent
8 option would best meet the mandate in the TREAD Act." Id. at
9 38704, 38722. "However," NHTSA noted, "it is possible that the
10 agency may obtain or receive new information that is sufficient
11 to justify a continuation of the options established by this
12 first part of this rule, or the adoption of some other
13 alternative." Id. at 38704; see also id. at 38722. NHTSA
14 therefore plans to issue the long-term requirements by March 1,
15 2005, after reviewing the public's new comments, the agency's new
16 findings, and any other information submitted by that date. Id.
17 at 38704, 38722. The long-term requirements would apply to
18 vehicles manufactured after October 31, 2006. Id. at 38704,
19 38722.

20 In addition to promulgating short-term requirements for
21 TPMSs, the agency introduced two different mandatory written
22 instructions for vehicle owner's manuals. Safety Standard, 49
23 C.F.R. § 571.138 pt. S4.5; see also Final Rule, 67 Fed. Reg. at
24 38727-28. These written instructions reflected the different
25 capabilities of direct, hybrid, and indirect systems. In
26 vehicles certified to the four-tire, 25 percent standard -- which

1 would presumably use direct or hybrid systems -- the owner's
2 manual must include the following statement:

3 When the tire pressure monitoring system
4 warning light is lit, one or more of your
5 tires is significantly under-inflated. You
6 should stop and check your tires as soon as
7 possible, and inflate them to the proper
8 pressure as indicated on the vehicle's tire
9 information placard. . . .

10 Safety Standard, 49 C.F.R. § 571.138 pt. S4.5.1; see also Final
11 Rule, 67 Fed. Reg. at 38727. In vehicles certified to the one-
12 tire, 30 percent standard -- which would presumably use indirect
13 systems -- the owner's manual must contain the following
14 statement:

15 **Note:** The tire pressure monitoring system on
16 your vehicle will warn you when one of your
17 tires is significantly under-inflated and
18 when some combinations of your tires are
19 significantly under-inflated. However, there
20 are other combinations of significantly
21 under-inflated tires for which your tire
22 pressure monitoring system may not warn you.
23 These other combinations are relatively
24 common, accounting for approximately half the
25 instances in which vehicles have
26 significantly under-inflated tires. For
27 example, your system may not warn you when
28 both tires on the same side or on the same
29 axle of your vehicle are significantly
30 under-inflated. It is particularly
31 important, therefore, for you to check the
32 tire pressure in all of your tires regularly
33 and maintain proper pressure.

34 Safety Standard, 49 C.F.R. § 571.138 pt. S4.5.2 (bold and italics
35 in original); see also Final Rule, 67 Fed. Reg. at 38728.¹⁷

¹⁷ The agency justified the latter requirement as an effort "[t]o avoid the creation of a false sense of security" in drivers of vehicles that rely on indirect systems. Final Rule, 67 Fed. Reg. at 38728; see also Respondent's Br. at 35.

1 Lastly, the agency supported the Final Rule with the
2 following cost/benefit analysis of the two short-term
3 requirements:

	Four-tire, 25 percent ¹⁸	One-tire, 30 percent ¹⁹
Fatalities prevented per year ²⁰	124	79
Injuries mitigated or prevented per year ²¹	8,722	5,176
Average net cost per vehicle ²²	\$53.87	\$44.13

The agency did not specifically discuss the efficacy of such warnings when contained in owner's manuals. Nor did the agency assess the dangers, if any, with regard to renters or borrowers of vehicles, who might be unlikely to see owner's manuals, and might therefore take false comfort from the tire pressure display on the dashboard of vehicles that rely on indirect systems.

¹⁸ The figures for the four-tire, 25 percent standard were based upon the agency's assumption that "[i]f all light vehicles meet the four-tire, 25 percent" standard, automakers would install hybrid systems in vehicles that were already equipped with ABS, and direct systems in vehicles that were not already equipped with ABS. Final Rule, 67 Fed. Reg. at 38740.

¹⁹ The figures for the one-tire, 30 percent standard were based upon the agency's assumption that "[i]f all light vehicles meet the one-tire, 30 percent" standard, automakers would install indirect systems in vehicles that were already equipped with ABS, and direct systems in vehicles that were not already equipped with ABS. Final Rule, 67 Fed. Reg. at 38740.

²⁰ The "fatalities prevented" and "injuries mitigated or prevented" figures "include deaths and injuries prevented due to reductions in crashes caused by blowouts and skidding/loss of control." Final Rule, 67 Fed. Reg. at 38708 n.6; see also id. at 38739.

²¹ See supra note 20.

²² Net cost equals the vehicle costs [i.e., the installation costs] plus the maintenance costs minus the fuel and tread wear savings. Final Rule, 67 Fed. Reg. at 38741; see id. at 38708 n.6, 38709 n.7, 38741.

1 2	Total net cost per year ²³ (millions)	\$862	\$706
3 4	Net cost per equivalent life saved (millions) ²⁴	\$4.3	\$5.8

5 Final Rule, 67 Fed. Reg. at 38740-41.

6 **DISCUSSION**

7 I. Standard of Review

8 The parties sharply dispute whether the Final Rule is
9 contrary to the intent of Congress as "unambiguously expressed"
10 in section 13 of the TREAD Act, see Chevron U.S.A. Inc. v.
11 Natural Res. Def. Council, Inc., 467 U.S. 837, 842-43 (1984), and
12 whether the Final Rule is "arbitrary and capricious" under the
13 APA, see Motor Vehicle Mfrs. Ass'n v. State Farm Mut. Auto. Ins.
14 Co., 463 U.S. 29, 43-44 (1983).

15 To the extent that we review the scope of the agency's
16 authority under the TREAD Act, our inquiry is governed by
17 Chevron:

18 When a court reviews an agency's construction
19 of the statute which it administers, it is
20 confronted with two questions. First,
21 always, is the question whether Congress has
22 directly spoken to the precise question at
23 issue. If the intent of Congress is clear,
24 that is the end of the matter; for the court,
25 as well as the agency, must give effect to
26 the unambiguously expressed intent of
27 Congress.

28 If, however, the court determines Congress
29 has not directly addressed the precise
30 question at issue, the court does not simply

²³ See supra note 22.

²⁴ See supra notes 13, 20, and 22.

1 impose its own construction on the statute,
2 as would be necessary in the absence of an
3 administrative interpretation. Rather, if
4 the statute is silent or ambiguous with
5 respect to the specific issue, the question
6 for the court is whether the agency's answer
7 is based on a permissible construction of the
8 statute.

9 467 U.S. at 842-43 (footnotes omitted); accord New York Pub.
10 Interest Research Group v. Whitman, 321 F.3d 316, 324 (2d Cir.
11 2003).

12 To the extent that we review the reasonableness of the
13 agency's actions under the APA, our inquiry is governed by State
14 Farm:

15 The scope of review under the arbitrary and
16 capricious standard is narrow and a court is
17 not to substitute its judgment for that of
18 the agency. Nevertheless, the agency must
19 examine the relevant data and articulate a
20 satisfactory explanation for its action
21 including a rational connection between the
22 facts found and the choice made. In
23 reviewing that explanation, we must consider
24 whether the decision was based on a
25 consideration of the relevant factors and
26 whether there has been a clear error of
27 judgment. Normally, an agency rule would be
28 arbitrary and capricious if the agency has
29 relied on factors which Congress has not
30 intended it to consider, entirely failed to
31 consider an important aspect of the problem,
32 offered an explanation for its decision that
33 runs counter to the evidence before the
34 agency, or is so implausible that it could
35 not be ascribed to a difference in view or
36 the product of agency expertise. The
37 reviewing court should not attempt itself to
38 make up for such deficiencies; we may not
39 supply a reasoned basis for the agency's
40 action that the agency itself has not given.
41 We will, however, uphold a decision of less
42 than ideal clarity if the agency's path may
43 reasonably be discerned.

1 State Farm, 463 U.S. at 43 (citations and internal quotation
2 marks omitted); accord Henley v. FDA, 77 F.3d 616, 620 (2d Cir.
3 1996); see also Arent v. Shalala, 70 F.3d 610, 614-16 (D.C. Cir.
4 1995) (discussing the relationship between Chevron and State
5 Farm).

6 II. The One-Tire, 30 Percent Standard

7 As we have noted, NHTSA's Final Rule provides
8 automakers with two options during the phase-in period: They may
9 either comply with the four-tire, 25 percent standard by
10 installing direct, hybrid, or improved indirect systems in new
11 motor vehicles, or comply with the one-tire, 30 percent standard
12 by installing currently available indirect systems in new motor
13 vehicles. Safety Standard, 49 C.F.R. § 571.138 pt. S4.2; Final
14 Rule, 67 Fed. Reg. at 38722-23. The agency found that indirect
15 systems do not warn drivers when two tires on the same side or
16 the same axle of the vehicle are significantly under-inflated, or
17 when all four tires are significantly under-inflated. Notice, 66
18 Fed. Reg. at 38987; Final Rule, 67 Fed. Reg. at 38716, 38718.
19 According to the agency's mandatory owner's manual statement,
20 these three combinations are "relatively common," such that
21 indirect systems do not warn drivers in "approximately half [of]
22 the instances in which vehicles have significantly under-inflated
23 tires." Safety Standard, 49 C.F.R. § 571.138 pt. S4.5.2; see
24 also Final Rule, 67 Fed. Reg. at 38718, 38728.

1 The petitioners' principal arguments are that the
2 agency's adoption of a one-tire, 30 percent standard is contrary
3 to the intent of the TREAD Act and, in light of the relative
4 shortcomings of indirect systems, arbitrary and capricious. We
5 agree on both counts.

6 A. The TREAD Act

7 The TREAD Act does not speak in terms of types of
8 TPMSs; it does not state whether the agency's rule must adopt
9 standards that require automakers to install direct, hybrid, or
10 indirect systems. It says only that "the Secretary of
11 Transportation shall complete a rulemaking for a regulation to
12 require a warning system in new motor vehicles to indicate to the
13 operator when a tire is significantly under-inflated." TREAD Act
14 § 13 (emphasis added).

15 The petitioners argue that the rule's one-tire, 30
16 percent standard fails to satisfy this minimum statutory
17 requirement by permitting automakers to install currently
18 available indirect systems, even though such systems do not warn
19 drivers when two tires on the same side or the same axle of the
20 vehicle are significantly under-inflated, or when all four tires
21 are significantly under-inflated. The agency responds that the
22 plain language of the TREAD Act requires only that TPMSs must
23 warn drivers when "a" tire is significantly under-inflated; it
24 does not expressly state that TPMSs must also warn drivers when
25 "two," "three," or "four " tires are significantly under-

1 inflated. The agency therefore suggests that the TREAD Act
2 requires no more than a one-tire TPMS standard.

3 We think that, in light of the language and purpose of
4 the TREAD Act, the petitioners' construction is clearly right and
5 the agency's construction is clearly wrong. Section 13 requires
6 warning systems that indicate "when a tire is significantly under
7 inflated." TREAD Act § 13 (emphasis added). The TREAD Act's "a
8 tire" plainly means one tire, two tires, three tires, or all four
9 tires, under the elementary rule of statutory construction that
10 the singular ("a tire") includes the plural (more than one tire).
11 See 1 U.S.C. § 1 ("In determining the meaning of any Act of
12 Congress, unless the context indicates otherwise . . . words
13 importing the singular include and apply to several persons,
14 parties, or things."); see also William N. Eskridge, Jr. & Philip
15 P. Frickey, Cases and Materials on Legislation 642-43 (2d ed.
16 1995) (discussing the rule). Obviously, if a vehicle has two
17 tires that are significantly under-inflated, then it has "a" tire
18 that is significantly under-inflated -- indeed, it has two
19 instances of "a tire" that is significantly under-inflated.²⁵

²⁵ If a statute mandated a requirement for warning systems in new motor vehicles that indicate when "a door" is open, it could hardly be argued that systems would comply with the statute by warning drivers when the driver's-side door or the front passenger-side door is open, but not when the driver's-side and the front passenger-side door are open.

Farther afield, Justice Scalia recently had occasion to comment that the elements of involuntary manslaughter are: "(1) the killing (2) of a human being (3) negligently." Neder v. United States, 527 U.S. 1, 31 (1999) (Scalia, J., concurring in part and dissenting in part) (emphasis added). It can hardly be

1 The purpose of the statute, moreover, is to prevent
2 motor vehicle crashes caused by significantly under-inflated
3 tires. It is contrary to that purpose to read the phrase, "when
4 a tire is significantly under-inflated," to mean "when one tire,
5 and only one tire, is significantly under-inflated," thereby
6 excluding "approximately half" of the instances in which tires
7 are significantly under-inflated, Safety Standard, 49 C.F.R.
8 § 571.138 pt. S4.5.2; see also Final Rule, 67 Fed. Reg. at 38718,
9 38728, and raising the risk that blowouts, flat tires, skidding,
10 loss of control, and increased stopping distances will cause
11 accidental injuries or deaths, Final Rule, 67 Fed. Reg. at
12 38739.²⁶

13 "The judiciary is the final authority on issues of
14 statutory construction and must reject administrative
15 constructions which are contrary to clear congressional intent."
16 Chevron, 467 U.S. at 843 n.9. We conclude that the agency's
17 reading of section 13 of the TREAD Act -- which permits the
18 agency to adopt a one-tire TPMS standard -- is contrary to the

said that, under this definition, the killing of two, three, or
four human beings negligently is not manslaughter; surely it is
two, three, or four instances of manslaughter.

²⁶ Indeed, as NHTSA itself explained, "the agency
tentatively believes that, in the long-term, the four-tire, 25
percent option would best meet the mandate in the TREAD Act and
best serve the American public." Final Rule, 67 Fed. Reg. at
38727; see also id. at 38718, 38738.

1 "unambiguously expressed intent of Congress." Chevron, 467 U.S.
2 at 843.²⁷

3 B. The APA

4 Moreover, even if the Final Rule were not contrary to
5 the intent of the TREAD Act, see id. at 842, we would conclude
6 that the agency's adoption of the one-tire, 30 percent standard
7 option was arbitrary and capricious, see State Farm, 463 U.S. at
8 43. In light of the administrative record, which documents the
9 relative shortcomings of currently available indirect systems, it
10 was unreasonable for NHTSA to adopt standards that allow
11 automakers to install such systems in new motor vehicles. Most
12 significantly, as NHTSA notes and as we have repeated more than
13 once, for each occasion on which an indirect system will detect
14 the presence of one or more significantly under-inflated tires,
15 there will be an occasion on which it will fail to detect them.
16 Safety Standard, 49 C.F.R. § 571.138 pt. S4.5.2; see also Final

²⁷ The intervenor argues that the petitioners' statutory challenge to the one-tire, 30 percent standard was not made with "sufficient clarity" during the rulemaking proceedings, and thus cannot be raised in this petition for review. Intervenor's Br. at 20. Whether or not the petitioners raised this specific issue in the rulemaking proceedings, however, the intervenor raised it and the agency addressed it. See, e.g., 67 Fed. Reg. at 38722 ("During [the phase-in] period, the agency requests that commenters address how the performance characteristics of particular types of TPMSs satisfy the [TREAD Act's] statutory requirement that systems provide a warning 'when a tire is significantly under-inflated.'"); id. at 38712, 38723 (analyzing the legislative history regarding "the type of TPMS that Congress intended to mandate" in section 13 of the TREAD Act); id. at 38723 (rejecting the intervenor's argument that Rep. Edward Markey (D-MA), the sponsor of the TPMS amendment, "intended that current indirect TPMSs be allowed" by the agency in the Final Rule).

1 Rule, 67 Fed. Reg. at 38728. Unlike direct systems, which work
2 in virtually every instance in which one or more tires are
3 significantly under-inflated, indirect systems do not warn
4 drivers in "about 50 percent" of those instances. Final Rule, 67
5 Fed. Reg. at 38718. Absent any "satisfactory explanation" in the
6 rulemaking record, the adoption of a standard that permits
7 installation of plainly inferior systems seems to us to be
8 arbitrary and capricious. State Farm, 463 U.S. at 43.

9 In the Final Rule, in the respondent's brief, and at
10 oral argument, the agency -- supported before us by the
11 intervenor and amicus curiae -- advanced three justifications for
12 adopting a safety standard that gives automakers the option to
13 install indirect systems: (1) the lower costs of installing
14 indirect systems in vehicles already equipped with anti-lock
15 braking systems, see Final Rule, 67 Fed. Reg. at 38706, 38725;
16 Respondent's Br. at 31-34, 36-38; (2) the need to encourage
17 innovation in indirect systems, see Final Rule, 67 Fed. Reg. at
18 38706, 38717, 38725, 38727, 38738; Respondent's Br. at 32, 38-41;
19 and (3) and the possibility that direct systems may be less
20 robust than indirect systems, see Respondent's Br. at 10, 31, 37.
21 We have carefully reviewed these arguments and the rulemaking
22 record upon which they are based. For the reasons set forth
23 below, we conclude that, in light of the rulemaking record, these
24 arguments are not "satisfactory explanation[s]" that "includ[e] a
25 'rational connection between the facts found and the choice

1 made.'" State Farm, 463 U.S. at 43 (quoting Burlington Truck
2 Lines, Inc. v. United States, 371 U.S. 156, 168 (1962)).

3 1. Costs. NHTSA seeks to justify the one-tire, 30
4 percent option by noting that, "for vehicles already equipped
5 with ABS, the installation of a current indirect TPMS is the
6 least expensive way of complying with a TPMS standard," Final
7 Rule, 67 Fed. Reg. at 38706, and by predicting that "[c]onsumers
8 will benefit from the resulting cost savings," id. at 38725; see
9 also Respondent's Br. at 31-34, 36-38.

10 When the agency issued the Final Rule, it included a
11 comprehensive cost/benefit analysis that compared (1) adopting
12 the four-tire, 25 percent standard alone with (2) adopting both
13 the four-tire, 25 percent and the one-tire, 30 percent options
14 together. See id. at 38739-41; see supra at [25]. The agency
15 estimated that adopting the four-tire, 25 percent standard alone
16 would save 45 more lives and prevent or mitigate 3,546 more
17 injuries per year than adopting both options together, at an
18 additional annual net cost of \$156 million, or an additional
19 average net cost of \$9.74 per vehicle.²⁸ The agency also

²⁸ Although these figures are not included in the Final Rule, we draw them from the agency's cost/benefit analysis. See generally Final Rule, 67 Fed. Reg. at 38740-41.

The agency's analysis proceeded from two basic premises. First, the agency assumed that if only the four-tire, 25 percent standard was available, automakers would install hybrid systems in vehicles with ABS and direct systems in vehicles without ABS. Id. at 38740. Second, the agency assumed that if both the four-tire, 25 percent and the one-tire, 30 percent options were available, automakers would install indirect systems in vehicles with ABS and direct systems in vehicles without ABS. Id. at

38740. Based upon these two assumptions, the agency estimated and compared the costs and benefits of two alternative "complete compliance" scenarios: first, "if all light vehicles meet the four-tire, 25 percent compliance option," id. at 38741 (as they would if all automakers were required to comply with the four-tire, 25 percent standard), and second, "if all light vehicles meet the one-tire, 30 percent compliance option," id. (as they would if all automakers could choose between the four-tire, 25 percent and one-tire, 30 percent options).

To calculate the economic costs and benefits under each scenario, the agency considered several factors, including vehicle costs (i.e., the initial costs of installing a TPMS in new motor vehicles), maintenance costs, testing costs, fuel economy benefits, and tread life benefits. Id. at 38740-41. In economic terms, the agency estimated that requiring automakers to meet the four-tire standard would incur a total annual net cost of \$862 million, or \$53.87 per vehicle, while permitting automakers to comply with both options would incur a total annual net cost of \$706 million, or \$44.13 per vehicle. Id. at 38741.

To calculate the safety benefits under each scenario, NHTSA estimated how many deaths would be prevented and how many injuries would be prevented or mitigated if the agency required automakers to meet the four-tire standard, or alternatively, if the agency permitted automakers to comply with both options. Id. at 38740. To do so, the agency predicted the extent to which the number of motor vehicle crashes caused by significantly under-inflated tires by preventing blowouts, flat tires, skidding, and loss of control, and by reducing stopping distances, especially on wet surfaces, would be reduced under each scenario. Id. at 38739. In safety terms, NHTSA estimated that if the agency required automakers to meet the four-tire standard, it would prevent 124 fatalities per year, and prevent or mitigate 8,722 injuries per year, whereas if the agency permitted automakers to comply with both options, it would prevent 79 fatalities per year, and prevent or mitigate 5,176 injuries per year. Id. at 38740.

Thus, NHTSA apparently concluded that requiring automakers to meet the four-tire, 25 percent standard would save 45 more lives and prevent or mitigate 3,546 more injuries per year, at an additional annual net cost of \$156 million, or an additional average net cost of \$9.74 per vehicle. These figures may be calculated by subtracting the costs and benefits of permitting automakers to comply with both options from the costs and benefits of requiring automakers to meet the four-tire standard, as follows:

(1) \$862 million per year - \$706 million per year = \$156 million per year

1 estimated that adopting the four-tire standard alone would cost
2 \$1.5 million less -- i.e., approximately 25 percent less -- per
3 equivalent life saved than adopting both options together. Final
4 Rule, 67 Fed. Reg. at 38741.²⁹ In other words, the agency
5 concluded that adopting the four-tire, 25 percent standard would
6 not only prevent more injuries and save more lives, but would
7 also be more cost effective on a per-life, per-injury basis than
8 adopting both options together.

9 These conclusions highlight what appears to us to be
10 the fundamental flaw in the agency's cost argument. The argument
11 is made without factoring in the substantial safety advantages of
12 direct and hybrid systems. The agency concludes that indirect
13 systems are less "expensive" to install in vehicles with ABS, id.
14 at 38706, but does not account for the fact that indirect systems
15 fail to warn drivers in "about 50 percent" of those instances in

(2) \$53.87 per vehicle - \$44.13 per vehicle =
\$9.74 per vehicle

(3) 124 fatalities per year - 79 fatalities
per year = 45 fatalities per year

(4) 8,722 injuries per year - 5,176 injuries
per year = 3,546 injuries per year

Final Rule, 67 Fed. Reg. 38740-41.

²⁹ See supra note 13 (explaining the "net cost per equivalent life saved"). These figures were calculated by comparing the net cost per equivalent life saved of adopting the four-tire standard alone to the net cost per equivalent life saved of adopting the two options together, as follows:

(1) \$5.8 million - \$4.3 million = \$1.5
million

(2) \$1.5 million / \$5.8 million = 25.8
percent

Final Rule, 67 Fed. Reg. 38740-41.

1 which tires are significantly under-inflated, Final Rule, 67 Fed.
2 Reg. at 38718; see id. at 38728; Safety Standard, 49 C.F.R.
3 § 571.138 pt. S4.5.2.

4 Of course, the agency was correct to consider the
5 relative costs of adopting or rejecting the one-tire, 30 percent
6 option. See, e.g., State Farm, 463 U.S. at 54 ("The agency is
7 correct to look at the costs as well as the benefits of Standard
8 208."); Ctr. for Auto Safety v. Peck, 751 F.2d 1336, 1343 (D.C.
9 Cir. 1985) ("The Safety Act's mandate is not . . . categorical.
10 Not all risks of accident or injury are to be eliminated, but
11 only those that are 'unreasonable,' and safety standards cannot
12 be imposed unless they are 'practicable.' This qualifying
13 language was added to ensure that NHTSA would 'consider
14 reasonableness of cost, feasibility and adequate lead time.'")
15 (citations omitted); S. Rep. No. 1301, at 6 (1966), reprinted in
16 1966 U.S.C.C.A.N. 2709, 2714 ("The committee recognizes . . .
17 that the Secretary will necessarily consider reasonableness of
18 cost, feasibility and adequate lead time."); H. Rep. No. 1776, at
19 16 (1966), quoted in State Farm, 463 U.S. at 55 ("In establishing
20 standards the Secretary must conform to the requirement that the
21 standard be practicable. This would require consideration of all
22 relevant factors, including . . . economic factors."). Yet a
23 conclusion that adopting a one-tire, 30 percent option is
24 cheaper, without more, does not satisfy the APA's arbitrary and
25 capricious standard. Presumably, one could design a still less
26 effective and less expensive warning system to monitor tire

1 pressure in new motor vehicles, but the lower price of such a
2 system, alone, would not justify adoption of an even less
3 rigorous TPMS standard.

4 The notion that "cheapest is best" is contrary to State
5 Farm. There the Court instructed NHTSA "to look at the costs as
6 well as the benefits" of motor vehicle safety standards, 463 U.S.
7 at 54, and to "bear in mind that Congress intended safety to be
8 the pre-eminent factor under the [Safety] Act," id. at 55 (citing
9 S. Rep. No. 1301, at 6, reprinted in 1966 U.S.C.C.A.N. at 2714
10 ("The Committee intends that safety shall be the overriding
11 consideration in the issuance of standards under this bill."); H.
12 Rep. No. 1776, at 16 ("Motor vehicle safety is the paramount
13 purpose of this bill and each standard must be related
14 thereto.")). Thus, when NHTSA issues standards under the Safety
15 Act, State Farm requires that the agency weigh safety benefits
16 against economic costs; moreover, State Farm instructs the agency
17 to place a thumb on the safety side of the scale. Yet we have
18 searched the rulemaking record here in vain for some "rational
19 connection between the facts found and the choice made." State
20 Farm, 463 U.S. at 43 (internal quotation marks omitted).

21 The agency chose to include the one-tire, 30 percent
22 option, even though adoption of the four-tire, 25 percent
23 standard alone was a more cost effective means of saving life and
24 limb. Whatever it means to treat safety as the "pre-eminent
25 factor," State Farm, 463 U.S. at 55, it must mean that the

1 economic advantages of a standard cannot be considered without
2 reference to the associated safety concerns.

3 It may, of course, be difficult to weigh economic costs
4 against safety benefits. The difficulty of the task, however,
5 does not relieve the agency of its obligation to perform it under
6 the Safety Act, section 13 of the TREAD Act, and State Farm. The
7 agency, instead, presents us with a rulemaking record that does
8 not explain why the costs saved were worth the benefits
9 sacrificed. And the record discloses that the added cost for a
10 system that worked all of the time, rather than half of the time,
11 was less than \$10 per car, and that the adoption of the four-
12 tire, 25 percent standard alone was the most cost effective means
13 of preventing crashes caused by significantly under-inflated
14 tires. Compare Final Rule, 67 Fed. Reg. at 38706, 38725 (the
15 agency's cost argument), with id. at 38740-41 (the agency's
16 cost/benefit analysis).

17 2. Innovation. NHTSA next argues that by "permit[ting]
18 manufacturers to continue to use current indirect TPMSs," id. at
19 38725, the one-tire option will "give manufacturers the
20 flexibility needed to innovate and improve the performance of the
21 indirect TPMSs," id., and "improve the chances that ways can be
22 found to improve the detection of under-inflation as well as
23 reduce the costs of doing so," id. at 38706. To support this
24 argument, the agency cites public comments from TRW Automotive
25 Electronics, Sumitomo Rubber Industries, and Toyota Motor
26 Corporation indicating that indirect systems could be improved to

1 satisfy higher performance standards. See, e.g., id. at 38710,
2 38716, 38725, 38727. As the agency notes, these comments
3 anticipate two types of improvements: the development of hybrid
4 systems, see id. at 38706, 38710, 38716, 38725, 38727, 38740, and
5 improvements to indirect systems themselves, see id. at 38710,
6 38727. Based on these comments, the agency argues that if
7 automakers are permitted to comply with the one-tire standard --
8 instead of being forced to comply with the four-tire standard --
9 they will be more likely to develop hybrid systems or improve
10 indirect systems during the phase-in period. See, e.g., id. at
11 38706, 38717, 38725, 38727, 38738; Respondent's Br. at 32, 38-41.

12 This argument, finding little or no support in the
13 rulemaking record, is not persuasive. The one-tire option might
14 permit innovation, but it also permits stagnation: It allows
15 automakers to install current indirect systems, without any
16 improvements, in all new motor vehicles. Final Rule, 67 Fed.
17 Reg. at 38706, 38717, 38725; Respondent's Br. at 14, 38-40. The
18 four-tire, 25 percent standard, were it the only one, would
19 require automakers to install direct systems, or to attempt to
20 develop new high-performance, low-cost alternatives, such as
21 hybrid systems or improved indirect systems, for installation in
22 new motor vehicles. Final Rule, 67 Fed. Reg. at 38717-18. In
23 light of these differences, it is difficult to understand -- and
24 the agency has not explained -- how adding the one-tire option

1 would encourage more "innovation" than adopting the four-tire
2 standard alone.³⁰

3 Moreover, the agency's innovation argument focuses
4 exclusively on the future of indirect and hybrid systems, but
5 neglects the future of direct systems. While the agency predicts
6 that hybrid systems could be developed, see id. at 38706, 38710,
7 38716, 38725, 38727, 38740, and that the performance of indirect
8 systems could be enhanced, see id. at 38710, 38727, it ignores
9 the possibility that the costs of direct systems could be
10 reduced.³¹ Perhaps, if the one-tire, 30 percent option were

³⁰ The cost/benefit analysis accompanying the Final Rule suggests the contrary result:

If all light vehicles meet the four-tire, 25 percent compliance option, the agency assumes that manufacturers will install hybrid TPMSs on the 67 percent of vehicles that are currently equipped with an ABS and direct TPMSs on the 33 percent of vehicles that are not so equipped. . . .

If all light vehicles meet the one-tire, 30 percent compliance option, the agency assumes that manufacturers will install an indirect TPMS on vehicles currently equipped with ABS (about 67 percent of new light vehicles), and a direct TPMS on vehicles not equipped with ABS (about 33 percent of new light vehicles).

Final Rule, 67 Fed. Reg. at 38740 (emphasis added). According to the agency's own cost/benefit analysis, in vehicles with ABS, the one-tire option would be satisfied by indirect systems -- which are currently available -- and the four-tire option would be satisfied by hybrid systems -- which are not now available, and thus, require innovation.

³¹ There was evidence in the rulemaking record to support the view that the maintenance costs of direct systems could be reduced. In two instances, the agency noted that "IQ-mobil Electronics, a TPMS manufacturer in Germany, commented that it has developed 'a batteryless transponder chip' that 'costs half

1 eliminated, the costs of producing and maintaining direct systems
2 would decline, as automakers sought more efficient ways to comply
3 with a four-tire standard. "Not having discussed the
4 possibility, the agency submitted no reasons" for us to reject
5 it. State Farm, 463 U.S. at 50.

6 In making this judgment, we are informed by the Supreme
7 Court's observation in State Farm:

8 [T]he [Safety] Act was necessary because the
9 industry was not sufficiently responsive to
10 safety concerns. The Act intended that
11 safety standards not depend on current
12 technology and could be "technology-forcing"
13 in the sense of inducing the development of
14 superior safety design. . . . [U]nder the
15 statute, the agency should not defer to the
16 industry's failure to develop safer cars
17

18 State Farm, 463 U.S. at 49 (citation omitted).

19 3. Robustness. In the Respondent's Brief and during
20 oral argument, NHTSA's counsel argued that the components of
21 direct systems are "less robust" than the components of indirect
22 systems, and "more susceptible to damage from road hazards and
23 routine maintenance, such as tire rotation." Respondent's Br. at
24 10; see also id. at 31, 37. In view of the agency's position

as much as the battery transmitter it replaces,' thus reducing
'high replacement costs for the tire transmitter.'" Final Rule,
67 Fed. Reg. at 38711; see also id. at 38741. In NHTSA's
cost/benefit analysis, the agency acknowledged that "the
maintenance costs associated with direct and hybrid TPMSs may
decrease significantly in the future if manufacturers are able to
mass produce a pressure sensor that does not require a battery."
Id. at 38741.

1 reflected in the Final Rule, we think this "robustness" argument
2 to be no more than a makeweight.³²

3 In the Final Rule, under the heading of "Unquantified
4 Costs," NHTSA anticipated that "there may be other maintenance
5 costs for both direct and indirect TPMS," Final Rule, 67 Fed.
6 Reg. at 38741 (emphasis added), citing the following examples:
7 "with indirect TPMSs, there may be problems with wheel speed
8 sensors and component failures," id., and "[w]ith direct TPMSs,

³² The history of the robustness argument is instructive. In 1981, when NHTSA terminated the earlier rulemaking proceedings on tire pressure warning devices, the agency cited public comments suggesting that "on-tire warning devices . . . are subject to road hazards, such as scuffing at curbs, ice, mud, etc." Termination, 46 Fed. Reg. at 43721; see also Final Rule, 67 Fed. Reg. at 38708. After the TREAD Act was enacted, in the Notice of Proposed Rulemaking, the agency seemed to analogize earlier on-tire devices to modern direct systems, opining that "the wheel components of direct TPMSs are less robust and more likely to sustain damage than the wheel components of indirect TPMSs, especially when tires are taken off the rim." Notice, 66 Fed. Reg. at 38988. NHTSA acknowledged, however, that there was no empirical evidence to support the robustness hypothesis: "The agency notes, however, that it has not received any information indicating that direct TPMSs have sustained damage during driving or tire maintenance." Id. NHTSA therefore requested comments on "the likelihood of such damage." Id.; see also Final Rule, 67 Fed. Reg. at 38711.

The agency received two comments addressing the robustness hypothesis: one from TRW Automotive Electronics, a manufacturer of direct and indirect systems, and another from Beru Corporation, a manufacturer of direct systems. Final Rule, 67 Fed. Reg. at 38711. TRW stated that "the likelihood of damage during driving or maintenance is unknown," and that "direct TPMS sensors are designed to minimize the likelihood of damage during driving or maintenance operations." Id. Beru stated that "it had sold over 800,000 direct TPMS wheel electronics and had received no reports of damage during operation or failures due to mounting error." Id. As we explain in the text, the agency expressly declined to draw any conclusions from these comments in the Final Rule. Id. at 38741.

1 the pressure sensors may be broken off when tires are changed,"
2 id. NHTSA said that it had "requested comments" on these
3 problems, "but received none." Id. "Without estimates of these
4 maintenance problems and costs," the agency did not "quantify
5 their impact." Id.

6 These remarks, agnostic as to the comparative
7 robustness of direct, hybrid, and indirect systems, do not
8 support counsel's suggestions in appellate briefs and during oral
9 argument that the components of direct systems are "less robust"
10 than the components of indirect systems, and "more susceptible to
11 damage from road hazards and routine maintenance, such as tire
12 rotation." Respondent's Br. at 10; see also id. at 31, 37. Once
13 NHTSA abandons an argument in a final rule, it cannot revive the
14 same argument for the purposes of safeguarding the rule from
15 judicial review. "The short -- and sufficient -- answer to
16 [NHTSA's] submission is that the courts may not accept appellate
17 counsel's post hoc rationalizations for agency action." State
18 Farm, 463 U.S. at 50 (citing Burlington Truck Lines, 371 U.S. at
19 168).

20 III. The Phase-in Period and the 25 Percent Option

21 In addition to challenging the agency's one-tire, 30
22 percent option, the petitioners target two other parts of the
23 agency's Final Rule: (1) the three-year phase-in period, see
24 Safety Standard, 49 C.F.R. § 571.138 pt. S7; Final Rule, 67 Fed.
25 Reg. at 38738; and (2) the "25 percent" aspect of the four-tire,
26 25 percent standard, see Safety Standard, 49 C.F.R. § 571.138 pt.

1 S4.2.1(a); Final Rule, 67 Fed. Reg. at 38705. These arguments
2 are without merit.

3 A. The Three-Year Phase-in Period

4 When the agency published the Notice of Proposed
5 Rulemaking, it noted that section 13 of the TREAD Act requires
6 that the Final Rule be issued by November 1, 2001, and take
7 effect by November 1, 2003. Notice, 66 Fed. Reg. at 38997. The
8 agency sought comment on "whether vehicle manufacturers will be
9 able to meet the statutory deadline, and whether TPMS
10 manufacturers will be able to supply enough TPMSs to meet the
11 demand under either of the alternatives proposed in this NPRM
12 [i.e., the four-tire, 20 percent standard, and the three-tire, 25
13 percent standard]." Id. In the commentary that followed, the
14 Alliance of Automobile Manufacturers -- the intervenors in these
15 proceedings -- proposed a more gradual phase-in period, to allow
16 for "sufficient 'prove-out'" of developing TPMS technologies.
17 Final Rule, 67 Fed. Reg. at 38737-38. "No commenter opposed a
18 phase-in of the TPMS requirements" during the rulemaking
19 proceedings. Id. at 38737.

20 When the agency issued the Final Rule, it accepted the
21 Alliance's comment, and "remain[ed] concerned that TPMS
22 manufacturers will not be able to produce enough systems and
23 parts to supply 16 million vehicles annually" by November 1,
24 2003. Id. at 38738. These findings, which the petitioners have
25 not disputed, plainly raise reasonable concerns. The agency's

1 adoption of a three-year phase-in period was not arbitrary and
2 capricious.

3 B. The "25 Percent" Aspect of the Four-Tire, 25 Percent Standard

4 As we have noted, in the Notice of Proposed Rulemaking,
5 the agency proposed two alternatives: a four-tire, 20 percent
6 standard, and a three-tire, 25 percent standard. Notice, 66 Fed.
7 Reg. at 38983. Then, in the draft final rule, the agency shifted
8 both standards, proposing an option for automakers to meet either
9 a four-tire, 25 percent standard or a one-tire, 30 percent
10 standard. Final Rule, 67 Fed. Reg. at 38717. The petitioners
11 argue that the agency's shift from 20 to 25 percent in the four-
12 tire standard was arbitrary and capricious. To support this
13 argument, the petitioners observe that according to the agency's
14 own findings, current direct systems are already able to detect
15 under-inflation levels equal to or greater than 20 percent.

16 As we have noted, however, the agency explained the
17 shift from a four-tire, 20 percent standard to a four-tire, 25
18 percent standard in the Final Rule:

19 The agency . . . adjust[ed] . . . the four-
20 tire option to 25 percent (instead of 20
21 percent) so that improved indirect TPMSs and
22 hybrid TPMSs could be used to comply with the
23 TPMS standard.

24 Id. at 38717-18. The agency supported this justification with a
25 cost/benefit analysis, which concluded that the net cost per
26 equivalent life saved of the four-tire, 20 percent standard was
27 between \$5.1 million and \$5.3 million, whereas the net cost per
28 equivalent life saved of the four-tire, 25 percent standard was

1 \$4.3 million. Id. at 38717. The agency concluded that "the
2 difference in benefits between TPMSs meeting four-tire, 20
3 percent requirements and TPMSs meeting four-tire, 25 percent
4 requirements should not be substantial." Id. at 38706. Given
5 that the 25 percent standard was substantially more cost
6 effective than the 20 percent standard, we conclude that it was
7 reasonable for NHTSA to adopt the former and reject the latter.

8 C. Other Arguments

9 In addition to these two arguments, the petitioners
10 also argue that the Final Rule is contrary to the intent of the
11 TREAD Act insofar as it (1) defines the term "significantly under
12 inflated" in contradictory ways by including both 25 percent and
13 30 percent options, and (2) permits many new motor vehicles to be
14 made without any TPMSs during the phase-in period, which extends
15 three years beyond November 1, 2003, the effective date
16 prescribed by the Act.

17 These arguments also lack merit. First, the TREAD Act
18 does not instruct the agency to define the term "significantly
19 under inflated" at all, let alone require the agency to define
20 the term as a specific percentage below placard pressure -- e.g.,
21 25 percent -- rather than as a range between two percentages --
22 e.g., between 25 and 30 percent. See TREAD Act § 13. Second,
23 the Safety Act expressly instructs the Secretary of
24 Transportation to issue "practicable" safety standards. 49
25 U.S.C. 30111(a). As we have explained, the agency found that it
26 would not be practicable to require TPMS manufacturers to produce

1 and automakers to install TPMSs in all new motor vehicles by
2 November 1, 2003. Final Rule, 67 Fed. Reg. at 38737-38.

3 **CONCLUSION**

4 We conclude that the agency's adoption of a one-tire,
5 30 percent option was both contrary to law and arbitrary and
6 capricious, and that the agency's adoption of the phase-in period
7 and the four-tire, 25 percent option were not. We grant the
8 petition for review, vacate the rule, and remand to the agency
9 for further rulemaking proceedings consistent with this opinion.

10 The mandate shall issue forthwith.